

Beam Clamp Rigging Rollers

Pipe rigging rollers are used for a variety of applications, in particular for installation of pipe into racks at refineries, power plants, and other industrial facilities.

**SAFER, FASTER, EASIER
INSTALLATION OR REMOVAL OF PIPE**



HSD12-200



HZ6-200



HZ2-100



HZD-100



HZDD60-200


SPECIFICATIONS

	HSD12-100 1-Ton Unidirectional	HZ6-200 1-Ton Unidirectional	HZ2-100 2-Ton Unidirectional	HZD-100 5-Ton Unidirectional	HZDD60-200 10-Ton Unidirectional
Load Capacity:	2,000 lbs	2,000 lbs	4,000 lbs	10,000 lbs	20,000 lbs
Diameter Range:	2" - 12"	2-3/8" - 24"	2" - 16" (2-32" optional)	2" - 42"	24" - 60"
Equipment Mass:	43 lbs	94 lbs	98 lbs	95 lbs	222 lbs
Shipping Dimensions:	15" x 10" x 5"	26" x 15" x 9"	31" x 19" x 26"	26" x 15" x 7"	41" x 16" x 11"

MDRN-100



MDR-200



MDR-700



Extra small footprint
or extra large capacity
options are available

Handles for safe & easy
lifting for installations

SPECIFICATIONS

	MDRN-100 1-Ton Multi-Directional	MDR-200 1-Ton Multi-Directional	MDR-700 2-Ton Multi-Directional
Load Capacity:	2,000 lbs	2,000 lbs	4,000 lbs
Diameter Range:	2" - 8"	2" - 24"	4" - 36"
Equipment Mass:	40 lbs	60 lbs	80 lbs
Footprint:	15" x 9" x 5"	15" x 22" x 6"	18" x 31" x 7"

Specifications subject to change; consult factory for all specifications.

Features & Options



High-grade urethane rolls for grip, protecting pipe coatings and shock absorption.

Handles for easy moving.

Quick clamp system for 5-12" structural beam flange range.



Available with jacking systems to load or offload rollers easily

Pipe Rack Installation Equipment

Pipe Rigging Jacks

Pipe lifting jacks are an easy to use, cost-effective, simple unit that makes pipe rack installations and repairs more efficient. They are completely mechanical, portable, light weight and will greatly reduce the chance of damaging pipe during lifting.



BCPJS15-100



BCPJS40-100

LOAD OR OFFLOAD ROLLERS EASILY!

SPECIFICATIONS

Load Capacity:

1,500 lbs

4,000 lbs

Diameter Range:

0" – 12"

0" – 18"

Beam Width:

5" – 10.5"

5" – 10.5"

Height Range:

12" – 24"
Screw Jack Adjustable

12" – 24"
Screw Jack Adjustable

Beam Size Height

8" – 15"

8" – 15"

Equipment Mass:

34 lbs

98 lbs

Footprint:

28" x 6.5"

29" x 8.5"

Pipe Roller Hangers

Pipe roller hangers are designed for suspended pipe where longitudinal pipe movement may occur due to thermal expansion or contraction and where vertical adjustments may be required.



YPRNC-16



YPRNC-18



YPRNC-20

SPECIFICATIONS

Load Capacity:

1,200 lbs

1,400 lbs

1,700 lbs

Diameter:

16"

18"

20"

Equipment Mass:

35 lbs

40 lbs

56 lbs

Footprint:

5" x 20" x 24"

6" x 22" x 27"

6" x 24" x 29"

Specifications subject to change; consult factory for all specifications.

